


Heavy Duty Steel Lintel CH70/100

Wall Construction	CAVITY WALL
Inner Leaf	100-115
Outer Leaf	100-102
Cavity	70-85
Loading Details	HEAVY

Specification

Product Code	Standard Length (mm)	SWL (kN) 1:1/19:1	Weight (kg)	Nominal Height (mm)
CH70/1000900	900	32	9.77	158
CH70/1001050	1050	32	11.39	158
CH70/1001200	1200	32	13.02	158
CH70/1001350	1350	32	14.65	158
CH70/1001500	1500	32	16.28	158
CH70/1001650	1650	32	17.90	158
CH70/1001800	1800	32	19.53	158
CH70/1001950	1950	48	26.46	158
CH70/1002100	2100	48	28.50	158
CH70/1002250	2250	45	30.51	158
CH70/1002400	2400	45	32.54	158



All ratios are shown inner to outer

- The SWL (safe working load) is based on the total UDL (uniform distributed load) over maximum span using 150mm end bearings.
- Standard lengths are available in 150mm increments up to 2400mm.
- When using the Catnic CH and CX Open Back ranges with concrete floors, always ensure that the blockwork is built tight against the inner vertical face, and that a mortar joint is added to the top of the blockwork so that the floor units have an even spread over the inner flange of the lintel.

Note: Whilst the above information is intended to offer general guidance regarding typical applications, it should not be considered as comprehensive. Requirements not fully covered by the above should be referred to our technical services department for individual consideration.

Catnic

Pontypany Industrial Estate Caerphilly CF83 3GL United Kingdom
 +44 (0)29 2033 7900 | catnic.technical@tatasteeleurope.com
www.catnic.com

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

© Copyright 2024 Tata Steel UK Limited.