

# Light Duty Steel Lintel CN100


Wall Construction	INTERNAL WALL
Inner Leaf	100
Outer Leaf	N/A
Cavity	N/A
Loading Conditions	LIGHT DUTY



## Specification

Product Code	Standard Length (mm)	SWL (kN)	Weight (kg)	Nominal Height (mm)
CN1001050	1050	10	3.91	50
CN1001200	1200	10	4.46	50

- The SWL (safe working load) is based on the total UDL (uniform distributed load) over maximum span using 150mm end bearings.
- Standard lengths are available in 150mm increments.



All ratios are shown inner to outer

**Note:** Whilst the above information is intended to offer general guidance regarding typical applications, it should not be considered as comprehensive. Requirements not fully covered by the above should be referred to our technical services department for individual consideration.

**Catnic**  
 Pontypandy Industrial Estate Caerphilly CF83 3GL  
 United Kingdom  
 +44 (0)29 2033 7900  
[catnic.technical@tatasteleurope.com](mailto:catnic.technical@tatasteleurope.com)  
[catnic.com](http://catnic.com)

**Tata Steel UK Limited**  
 18 Grosvenor Place, London, SW1X 7HS  
 Registered in England No. 02280000

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

© Copyright 2025 Tata Steel UK Limited